

Recognition Systems HandPunch_® 4000 Biometric Time & Attendance Terminal

Full function time & attendance . . . at the palm of your hand.

The HandPunch[®] 4000 brings the flexibility of a full function time and attendance terminal together with the sophistication of the most accurate identification technology available. Using Ingersoll Rand Recognition Systems' field-proven hand geometry biometric technology, the HandPunch 4000 uses the size and shape of your employee's hand to verify their identity each time they punch. No fingerprints or palm prints are utilized.

A cost-saving, easy-to-use solution

With the HandPunch 4000, your hand is your badge. The cost of creating and administering badges is eliminated along with buddy punching. The system ensures payroll accuracy by simply requiring each employee to be there to punch. The terminal is fast and easy for anyone to use. An employee's identity is verified in less than one second.

An important HR communication tool

More than a simple time and attendance terminal, the HandPunch 4000 lets you tailor the system to meet your precise needs. The system provides the ability to send messages to employees when they punch. In addition, employees can view up to 24 information fields to find out about their schedule, total hours worked, and more.



FEATURES & BENEFITS

- Provides the most accurate time and attendance solution available
- Fast and easy to use
- Complete flexibility through 10 data management keys
- Eliminates badges
- Eliminates buddy punching
- Reduces supervisor workload

10 Programmable Data Management Keys

Ten user-definable data management keys let you collect and/or display data as employees punch. Common data collection uses include department transfers, tips collected, job codes, or pay codes. The keys can also be defined to allow employees to review punches or find out about their schedules, vacation time accumulated, hours worked, and other programmed information. To reduce keystrokes, the keys can also be set to automatically enter data such as a frequently used department number or in/out status.

Other data management key features include

- Employee messaging
- Review of employee information fields
- Validation tables to ensure proper data entry
- Restrict employee access to specific data management keys
- User defined prompts
- Multi-level input sequence definable per key
- Decision menus to minimize keystrokes

Schedules by Employee

Employee schedules may be downloaded to the HandPunch 4000 to restrict the times that an employee can punch. This can reduce unauthorized overtime as well as early "in" punches. A separate schedule can be defined for each employee providing the ultimate in flexibility.

Built-in Bar Code Reader

Some installations require the use of a badge. For these situations, the HandPunch 4000 includes an integrated bar code reader that can be used for ID number entry. The swipe-type reader supports the most popular bar code formats and allows for infrared badges.

Communications and Networking

Whether your needs are to network two terminals or thousands, the HandPunch 4000 can be configured to meet your needs. Standard RS-485 communications makes networking terminals easy and reliable. Options include an Ethernet Communications Modules and a high speed internal modem for remote sites. Each unit also provides RS-232 serial printer support.

Edit-at-the-Clock Functions

The HandPunch 4000 allows supervisors to override user restrictions and to input such items as missed punches, planned vacations, and sick time at the terminal. The password-protected mode provides greater supervisor flexibility by lessening the need for computer edits. Audit trails documenting the use of these functions are generated to ensure security.

Bell Schedules

The bell schedule lets you program the day, time, and duration of a series of bells. The bells can be programmed to signal the beginning or end of a shift, lunch, or break.

Door Control

The HandPunch 4000 provides the capability to unlock and monitor a door. An employee's individual schedule may be used to restrict access.



SPECIFICATIONS

	SPECIFICA	TIONS
	8.85 in (22.3 cm) wide 11.65 in (29.6 cm) high 8.55 in (21.7 cm) deep	
Weight: Power:		kg) ′DC or 12 to ⊢60 H7 watts
Environment:	Operating (0°C to 45 Relative H Non-opera 14°F to 14	: 32°F to 113°F 5°C) umidity: 20% to 80% NC ating (storage): 40°F (-10°C to 60°C)
Verification Times		umidity: 5% to 85% NC
Verification Time:		one second
Memory Retention:	Up to 5 ye	ars via the standard
Transaction Storage		hium battery.
Transaction Storage: ID Number Length:	7680 trans	
User Capacity:		gits from keypad or card
Template Size:	530 users expandable to 3,498 users 9 bytes	
Communications:	RS-485 (4 and 2 wire)	
communications.	RS-232 Serial Printer Support	
		communications
Baud Rate:	300 to 28.	
Card Reader Input:		
		(5 VDC provided by HandReader)
Card Reader Output:	Wiegand, Magnetic Stripe, Bar Code	
a Management Keys:	10 keys, user definable	
<u> </u>	Supports:	
	Validatio	n tables
	Employe	e information fields,24 max
		/el prompting
		iction by employee
	Decision Menus	
Punch Review		
Employee Messaging:	32 characters per message per employee	
Employee Name:	16 characters	
Employee Schedule:	Schedules definable for each employee	
rnal Barcode Reader:	Code 39	
	Interleaved 2 of 5	
Door Controls: Door Lock Output		
		-24VDC, 100mA max.)
		ch Monitoring
	Bell Ring (
Ontioner	(SINKS U	-24VDC, 100mA max.)
Options:		Operational Battery Backup
	DC-102	Data Converter (RS-232 to RS-485)
	EM-805	Memory Expansion - 3,498 users
	EN-200	Ethernet Communications
	LIN 200	Module
	MD-500	Internal 14.4 Baud Dial-up
	000 000	Modem
	WAR-FXT	1 year extended warranty
		year extended warranty

Data

E

Inter

For more information contact:



Moving You from **Punch** to **Paycheck** www.mwtime.com

800-383-7756

HandPunch® is a registered trademark of Ingersoll Rand Recognition Systems Specifications subject to change. Please check with your system vendor for details.

© 2006 Ingersoll Rand Company Limited Pub No. RS-TA-1479